

Physics 110 Lab 4: Projectile Motion

Name _____

Section _____

Date _____

Introduction

In this lab, we will study the motion of small plastic balls fired from a spring-powered projectile launcher. You will use two different methods to determine the velocity of the balls as they leave the launcher, and use that velocity, together with the equations governing projectile motion, to predict the range of a projectile fired at some arbitrary angle. As a test of your prediction, you will be asked to use the prediction to place a target on the floor at the spot where the ball will land.

Along the way, you will also investigate some new techniques of error analysis, and the differences between systematic and random errors.

Apparatus

The apparatus for this lab consists of a spring-powered projectile launcher which will fire a small plastic ball into the air. The goal of the lab is to determine the velocity of the ball leaving the launcher, and use that velocity to predict the flight of the ball when the launcher is used to fire the ball across the room.

For the first part of the experiment, the launcher will be fired straight up into the air. Place the launcher on the floor, and make sure the protractor reads 90° , and that the screws holding the launcher to the mount are tightened down. Make sure that the launcher is not aimed at a light (launchers which are mistakenly fired on the “high” setting will fire a ball into the ceiling hard enough to shatter light bulbs and make a mess), set the launcher to the “medium” setting (the second notch down), and fire the ball by tugging sharply on the launch cord. When firing the launcher, be sure to hold it down with your free hand.

Procedure

Part 1: Muzzle Velocity from Time of Flight

(a) One method you can use to find the velocity of a ball leaving the launcher is to measure the time it takes for the ball to reach its maximum height. Fire the launcher straight up, and use a stopwatch to measure the time between the firing of the launcher and the highest point the ball reaches. Each member of your group should repeat the measurement a total of ten times. Enter the time of flight for **your own measurements only** in the table below. Also, use Excel to determine the average and standard deviation of the repeated measurements and record the results in the table.

Trial	Time (s)
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
Avg.	
St. Dev.	

(b) Using the equations governing free-fall motion and the average value of the time of flight you obtained, calculate the initial velocity of the ball when it left the launcher in the space below. Also, determine the uncertainty in the velocity from the standard deviation of the time of flight measurements and record the final answer in the form $v \pm \Delta v$ in the space below.

Part 2: Muzzle Velocity from Maximum Height

(a) A second method of determining the initial velocity is to instead measure the maximum height reached by the ball. You may need to stand on the table in order to read the height. Take a few practice shots to determine the best way to read the ball's height using the meter stick, then each member of your group should record ten values of the maximum height reached. Enter the maximum height for **your own measurements only** in the table below. Also, use Excel to determine the average and standard deviation of the repeated measurements and record the results in the table.

Trial	y_f (m)
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
Avg.	
St. Dev.	

(b) Using the equations governing free-fall and the average value of the maximum height to calculate the initial velocity of the ball when it leaves the launcher in the space below (remember to include the height of the launcher in your calculation). Also, determine the uncertainty in the velocity from the standard deviation of the maximum height measurements and record the final answer in the form $v \pm \Delta v$ in the space below.

(c) Do the muzzle velocities determined in Parts 1 and 2 agree within experimental uncertainties? If not, explain why. Which value do you have more confidence in and why?

Part 3: Projectile Motion

(a) Clamp the projectile launcher to the edge of your lab table and set it up to launch the projectile horizontally. Make sure that the launcher is pointing in a direction such that the projectile can travel 2 m without hitting anything. Measure the height of the muzzle from the floor and record it below along with an estimated uncertainty as $y \pm \Delta y$.

(b) Using your best value for the muzzle velocity and the equations for projectile motion, predict where the projectile will land on the floor (the final x position) in the space below. Also, determine the uncertainty in this value from the uncertainties in v and y and record the final result in the form $x \pm \Delta x$.

(c) Cut a circular piece of paper with a diameter of $2\Delta x$ and place it on the floor at the position x . Then fire the projectile at the target. Did you hit it?